

# Anker SOLIX C1000 Portable Power Station

1056Wh | 1800W

InfiniPower™

GaNPrime™



TotalGuard™

SurgePad™

*Full Speed to Go ,  
Full Power to Last*



# Highlights

## InfiniPower™ 10 Years of Everyday Use

LiFePO4 batteries offer a 6× longer lifespan than the average power station. Designed for a decade of daily use, with an industry-leading 5-year device warranty

## HyperFlash™ Fast Recharge

You don't have a second to waste. Whether you've got a big trip or bad weather is on the horizon, Anker SOLIX C1000 recharges to 100% in just 58 minutes.\* That's 27.5% faster than power stations with the same capacity for ultra-fast, worry-free recharging.

## Power Anything with SurgePad™ Technology

Sip on freshly brewed coffee and grill up breakfast at the same time. With SurgePad™ Technology, You have up to 2400W output that powers 99% of appliances.



# Features

## **Proven Durability TotalGuard™**

Our drop-proof design and material selection meet the requirements of industry testing standards to withstand any impact during outdoor adventures.

## **Pro UPS**

Ensure continuous power with Uninterruptible Power Supply (UPS) Switchover time in under 20ms.

## **15% Smaller Than Industry Average**

You don't need to do any heavy lifting. Anker SOLIX C1000 is more compact and just as powerful as similar-capacity LFP power stations.

## **Flat Top for Extra Space**

Give yourself some extra room thanks to the flat design of Anker SOLIX C1000. You can set your devices or batteries on top, just like a desk.

# Specifications

## Product Model

PN	A1761
Model Name	Anker SOLIX C1000 Portable Power Station

## Battery Info

Type of Battery	LiFePO4
Capacity	1056Wh
Capacity	330000mAh
Cycle Life	3000+ (to 80%)



# Specifications

## Power Outputs

Maximum Output	1800W
# of Output Ports	11 (For US/JP/CA); 9 (For EU/UK/MEA/AU/CN)
# of Standard AC Socket	6 (For US/JP/CA) ; 4 (For EU/UK/MEA/AU/CN)
AC Rated Power	1800W
AC Surge Power	2400W
AC Total Output	1800W; Surgepad 2400W
AC Auto Shut-Off	standby mode 12h
# of USB-A Output	2

USB-A Rated Power (per port)	5V=2.4A (12W Max)
USB-A Total Output	24W
# of USB-C Output	2
USB-C Rated Power (per port)	5V=3A/ 9V=3A/ 12V=2.5A (30W Max) 5V=3A/9V=3A/15V=3A/
USB-C Total Output	130W
USB auto shut-off	Yes
# of Car Outlet	1
Car Outlet Rated Power (per port)	10.8~14V=10A (120W Max)

# Specifications

## Power Inputs

Input Voltage	100-120V (US/CA/JP) 220-240V (UK/EU/MEA/CN/AU)
Total Input Power	1300W (AC Direct)
EST Recharge Time	Default AC recharging: 90min(1000W) Ultra Fast AC recharging: 58min(1300W) Car socket recharging: 10.7h(120W) solar recharging: 1.8h(600W)
Use Ports While Recharging	Yes
Direct AC Input	Yes
Maximum AC Input Power	1300W
# of DC Input	1
DC Adapter	No
DC Adapter Input Power	-

EST DC Adapter Recharge Time	10.7 hrs (120W Car Charger)
DC Input Size	XT-60
Solar Input Power	11-32V $\equiv$ 10A; 32V-60V $\equiv$ 12.5A (600W Max)
EST Solar Recharge Time	6.1 Hours (2*100W) 4 Hours(3*100W) 3.6 Hours(2*200W) 2 Hours(3*200W) 1.8 Hours (2*400W)
Solar Panel Compatible	Yes
MPPT Support	Yes

**Sales Market: US/CA/JP/EU//UK/AU/TW/CN/MEA**

# Specifications

## Illumination Information

Flash Light	-
Flash Light Mode	-
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode (3 Level) SOS Mode

## Safety Information

Operation Temperature (°C/°F)	Charging: -20 -40°C / -4 -104°F Recharging: 0-40°C / 32-104°F
Overload Protection (AC)	>1800W
Over-current Protection (USB-A)	>2.4A
Over-current Protection (USB-C)	>3.6A (30W) >6A (100W)
Over-current Protection (Car port)	>10A

## Package Content

AC Adapter	-
Cable	AC Charging Cable 150cm Car Charging Cable 300cm Solar Charging Cable (1 to 2) 170cm

## Weight & Dimension

Product Dimension (mm)	376x205x267 mm
Packaging Dimension	Packaging 451x274x310mm UN BOX 464x287x330mm
Product Weight	12.9 kg ; 28.44 lb
Product Weight with Package	14.1 kg ; 31.09 lb