

# DELTA 3 Max Plus (2048Wh)

Colour: Silver

Capacity: 2048Wh

Net Weight: Approx. 22.1 kg

Dimensions: 494 × 242 × 305 mm

Total Output Ports: 10

Total Output Power: 3581W Max

UPS: 10 ms + HID

Warranty Period: 3+2 years

Volume: 600W ≤ 25 dB



## AC Output

Number of AC Outlets

4

Output Priority

Yes

Max AC Output

3000W

Surge Output

6000W

X-Fusion

Yes

Max X-Boost Output

3900W

Output Voltage

230V~50Hz, 3000W Total 13A Max per port (×4)

## DC Output

Number of DC Outlets

6

USB-A

1 × 18W Max

USB-C

1 × 140W Max (HID)

2 × 45W Max (Total 45W)

12V DC Output

378W Max Car Power Output × 1:12.6V==10A Anderson Output × 1:12.6V==30A

## Input

Utility Power Charging

2300W  
(Depending on Input Voltage)

Input Voltage

220-240V~10A  
50/60Hz

0-80% Charge Time

47 min

Solar Charging

1000W  
(2 × 500W)

Alternator Charging

1000W Max  
Through 4+8 Port

0-100% Charge Time

68 min

Generator Charging

2400W Max

Car Charging

12V/24V==8A

## Battery

Battery Chemistry

LFP

Type of Extra Battery Ports

4+8

CTC Technology

CTC

Extra Battery Compatibility

D2M/D3MP  
D3/DP3 EB

Number of Extra Battery Ports

1(expandable to 2)

Max Capacity with Extra Battery

Up to 10kWh  
with 2 × DELTA Pro 3 Extra Battery

## Connections

Screen

Yes

Wi-Fi

Yes

Bluetooth

Yes

App

Yes

## Operating Conditions

Operating Altitude: ≤3000 m

Charge Temperature: 0-45°C

Discharge Temperature: -10-45°C

Storage Temperature: -10-45°C